

UV GUARD® MORTAR MATCH

UV GUARD Mortar Match is a highly elastic, non-structural finish formulated from 100 percent pure acrylic resins. It was specifically developed to seal existing mortar joints and other construction related areas where maximum elasticity or moisture protection is required and/or where a textured appearance is desired.



www.weatherall.com

Manufacturing Facility:
Weatherall Company, Inc.
106 Industrial Way
Charlestown, IN 47111
1-800-367-7068
Fax: 812-256-2344

Distribution Centers:
Colorado: 800-430-7074
Georgia: 866-399-6553
Utah: 866-658-1312

USES

- **New Construction**
UV GUARD Mortar Match is used as a weather-tight seal over new mortar joints where a positive, flexible seal is needed and a neat, mortar textured finish is desired.
- **Restoration**
UV GUARD Mortar Match is an excellent restoration/repair product for previously applied mortar. Its elasticity is ideal for sealing over cracked and deteriorated mortar joints, eliminating air and water infiltration.

ADVANTAGES

- **Unsurpassed Elasticity**
- **Stays Flexible**
Withstands repeated expansion and contraction caused by severe temperature extremes and moisture.
- **Impenetrable Seal**
Adheres permanently to surfaces to form an airtight seal that prevents air and water infiltration.
- **Durable**
Forms a tough, protective, damage resistant surface that will remain in place for many years. Will not tear or pull away.
- **UV Resistant**
Resists ultraviolet degradation and has superior color retention.
- **Non-toxic**
May be used safely on the interior as well as the exterior. No odor when dry.
- **Warranty**
Carries a limited lifetime warranty.

TECHNICAL INFORMATION

Available Colors

UV GUARD Mortar Match is available in a wide range of colors to either imitate the traditional look of mortar or to blend in with the tones of the brick or stone. Custom colors are also available.

Texture

UV GUARD Mortar Match is available in a semi matte sand texture. The product can be tooled to achieve a semi-smooth to rough finish.

Recommended Thickness

Finish troweled thickness should be approximately 1/8" - 3/16" over existing mortar joints. The thickness can be increased to 5/16" - 1/4" across the face of the joint if a backer rod is used.

Physical Properties

Composition	Textured Acrylic Latex
Viscosity	Trowel Grade
Density	14.5 lbs/gal
VOC	25g/l
pH	8.5-9
% Solids	84%
Elongation	50%
Temperature Range	-40° F. to 250° F.
Odor	Odorless when dry
Toxicity	Non-toxic
Shelf Life	2 Years
Stability	Salt spray stable
Test Procedure	ASTM-C834

Coverage

The coverage guide on the back of this page is offered to assist in estimating coverage and quantities required. Measure the total number of linear feet and estimate the average width of the finished joint, both interior and exterior.

Drying Time

UV GUARD Mortar Match will be skinned over in approximately 30 minutes and will be surface dry within 8-10 hours under normal conditions. It will be fully cured in 7-10 days. Actual times will vary depending on temperature and relative humidity. UV GUARD Mortar Match should be protected from contact damage for at least 1 week after application.

Packaging

UV GUARD Mortar Match is available in Five gallon pails and 10.3 oz. cartridges.

Storage

UV GUARD Mortar Match must be protected from freezing and stored in temperatures that do not exceed 90° F. Do not store in direct sunlight. Opened container may be stored by floating a thin film of water (1/16") on the surface of the material, covering it with plastic and tightly relidding the container.

Clean Up

Immediately clean up uncured UV GUARD Mortar Match with soap and water. Do not allow material to dry on tools, caulking guns, pump or clothing.

APPLICATION GUIDELINES

READ AND FOLLOW ALL LABEL INSTRUCTIONS PRIOR TO APPLICATION OF THE PRODUCT.

Surface Preparation

Surface must be dry, clean, structurally sound and free from grease, paraffins, oils, urethanes, or other contaminants that could inhibit the ability of the material to bond to the substrate. Any finish, whatever the composition, may be incompatible with UV GUARD Mortar Match if the finish deposits a heavy film on the substrate. UV GUARD Mortar Match must be able to bond to the substrate. If a film forming sealer is already applied to the substrate, it must be removed prior to application of the material.

NOTE: Some finishes will leave a film on the surface that can adversely affect the adhesion of the UV GUARD Mortar Match. Finishes that contain oils, petroleum distillates, paraffins, urethanes, or any other finish that is film forming or very freshly applied may not allow the UV GUARD Mortar Match to properly bond.

If you are in doubt as to the compatibility of UV GUARD Mortar Match with a previously applied preservative or sealer, please contact Weatherall technical support prior to the application of UV GUARD Mortar Match.

Application Temperature

UV GUARD Mortar Match should not be applied when temperatures are below 40° F. or when subfreezing temperatures are expected within 48 hours of application. Avoid application of UV GUARD Mortar Match in rain or when rain is imminent. When applying UV GUARD Mortar Match in very hot weather, it is recommended that the material be applied to the shaded side of the house.

NOTE: There may be occasions when application of UV GUARD Mortar Match in subfreezing temperatures is unavoidable. In such cases, contact your Weatherall representative for specific recommendations. DO NOT APPLY ON FROZEN SURFACES! UV GUARD Mortar Match should not be applied to hot or sun-baked surfaces. Try to apply to cool or shaded surfaces.

Application

UV GUARD Mortar Match can be applied with a bulk loading caulking gun or 10.3 oz cartridge. **Do not thin this product with water.** Apply a bead of UV GUARD Mortar Match as needed to cover the joint. Apply uniform pressure to the trigger to form a smooth, even bead. Tool bead to a smooth finish. The tooled bead should be firmly troweled into edges to ensure complete edge adhesion. For best results, cured beads should be between 1/8" and 1/4" deep. For best performance the substrate should be sealed **after** the UV GUARD Mortar Match has been applied and properly cured.

NOTE: To tool bead use a trowel and spray back of trowel with release agent (50/50 water and isopropyl alcohol). This will allow the trowel to glide smoothly over the material.

AVAILABILITY / SUPPORT

Weatherall products are available from the manufacturing plant and distribution centers, as well as a national network of distributors. Weatherall Company will gladly provide technical support upon request.

LIMITED LIFETIME WARRANTY

Warranty Statement:

Weatherall Company, Inc. warrants satisfactory results from the use of UV GUARD Mortar Match when installed in accordance with the application instructions provided by Weatherall.



Exceptions: This warranty does not cover failures due to the following: Fire, flood, natural disaster or any acts of God; improper storage, handling or installation; plumbing leaks, faulty construction or settling that would exceed the material's normal elasticity.

Claims Notification: Notification of claims must be made in writing to Weatherall Company, Inc. and accompanied by the sales receipt. If UV GUARD Mortar Match is proved to have failed, Weatherall Company, Inc., at its own discretion, will replace the failed material or refund the purchase price of the material only. Weatherall Company, Inc. reserves the right to inspect the jobsite by an authorized representative prior to the settlement of any claims.

Weatherall's sole and complete responsibility for proved material failure is as set forth in this warranty. Weatherall Company, Inc. will not be responsible for incidental, indirect or consequential damages including reinstallation labor. The user is solely responsible for determining the suitability of this product for its intended use prior to application. User assumes all risk and liability in connection therewith. Questions concerning this warranty should be directed to the nearest Weatherall representative.

UVGMM0207

ESTIMATING GUIDE FOR UV GUARD MORTAR MATCH

Finished Joint Width	5 Gallon Pail	10.3 oz. Cartridge
1/2" @ 1/8" thickness	3000'	60'
1" @ 1/8"-3/16" thickness	770'-513'	15'-10'
1 1/4" @ 1/8"-3/16" thickness	616'-411'	12'-8'
1 1/2" @ 1/8"-1/4" thickness	514'-257'	10'-5'
1 3/4" @ 1/8"-1/4" thickness	440'-220'	9'-5'
2" @ 3/16"-1/4" thickness	256'-192'	5'-4'
2 1/2" @ 3/16"-1/4" thickness	205'-154'	4'-3'